


PITBULL POWER



**PRODUCT
CATALOGUE**

LITHIUM-ION BATTERIES

ABOUT BRAND

Inhouse R&D

Our in-house R&D drives innovation, ensuring top-quality lithium-ion batteries through advanced materials and manufacturing to meet evolving market demands.

Key Areas of Focus in Our In-House R&D:



Advanced Materials Development:

Our R&D team is dedicated to exploring and optimizing new materials for our battery.



Battery Efficiency and Performance:

Our R&D enhances battery efficiency, ensuring maximum energy storage, stability, and durability through continuous testing and innovation over thousands of cycles.



Safety and Thermal Management:

We prioritize battery safety with advanced thermal management, enhanced BMS, and safety protocols to prevent overheating, thermal runaway, and external damage.



Manufacturing Process Optimization:

Efficiency in the manufacturing process directly impacts both cost and quality. By integrating high quality machines, we are able to improve production speed, reduce defects and ensure quality control.



Customized Solutions for Specific Applications:

Our in-house R&D customizes batteries to meet industry-specific needs, from EVs and renewable storage to consumer electronics and beyond.

Our in-house R&D and vertically integrated approach ensure full control over development, enabling efficient delivery of high-quality, reliable, and cost-effective lithium-ion batteries tailored to customer needs.

State of the Art Manufacturing Facility

At Pitbull Power, we operate a cutting-edge manufacturing facility that incorporates the latest advancements in battery production technology. Our state-of-the-art plant is designed to meet the highest standards of efficiency, precision, and safety, ensuring that each lithium-ion battery we produce is of the highest quality.

By leveraging the latest innovations in battery technology and manufacturing processes, our facility ensures that we consistently deliver high-performance, long-lasting batteries that meet the needs of industries such as electric vehicles, renewable energy storage, and consumer electronics.

After-Sales Support

We believe that exceptional customer service doesn't end after the purchase, it's just the beginning. Our after-sales support is designed to ensure that you get the most out of your lithium-ion batteries, with peace of mind throughout their lifecycle. We promise to provide prompt and reliable assistance, whether it's for product installation, troubleshooting or performance optimization.

Our dedicated support team is available to answer any questions and resolve any issues efficiently. We offer comprehensive warranty services, technical support, and product maintenance to ensure your batteries continue to perform at their best. Our goal is to build lasting relationships with our customers by delivering ongoing support that goes beyond the sale, ensuring your complete satisfaction and confidence in our products.



E-RIKSHAW BATTERY



High Energy Density



Long Cycle Life



Fast Charging



Fire Resistant

E-RIKSHAW BATTERY

PPL51100ER

* Standard as per AIS156



RATING

Voltage Ratings (Volts) : 51.2
Battery Capacity (Ah) : 100
Power Rating (kWh) : 5.12



COMMUNICATION OPTIONS

- Bluetooth
- CAN (Optional)
- UART/RS485 (Optional)
- IoT (Optional) - Cloud Storage, Real Time Performance Analytics, Battery Swapping Analytics, Asset Tracking, SOC Monitoring, Fleet Management



ELELCTRICAL PARAMETERS

- Operating Voltage Range (Volts) : $44.0 \sim 58.4 \pm 1.0$
- Maximum Charging Current : 0.5C
- Maximum Discharge Current : 1C Continuous



CELL CYCLE LIFE

≥ 2000



BMS PROTECTION

- Over-charge Protection
- Over-discharge Protection
- Over-current Protection
- Over-temperature Protection
- Short-circuit Protection
- Audio & Visual Alarm



BALANCING MODE

ACTIVE



CHARGER SPECIFICATION

- Charging Voltage (Volts) : 58.0 ± 0.5
- Charging Current (Amps) : 30.0 ± 0.5
- Charging Mode : Precharge - CC - CV
- CAN Enabled (Optional)
- LED Display (Optional)
- Earth Leakage Protection
- Reverse Polarity Protection
- Failure Sensing



OPERATING CONDITIONS

- Charging Temperature (Deg.C) : $-5 \sim 55$
- Discharging Temperature (Deg.C) : $-10 \sim 60$
- Storage Temperature (Deg.C) : $0 \sim 35$



OUTPUT INTERFACE

SB 75 / SB 50



WEATHER SEALING RATING

IP67



FIRE RESISTANCE

YES



KEY FEATURES

- High Energy Density
- Long Cycle Life
- Fast Charging
- Low Self-Discharge
- Smart Battery Management

E-RIKSHAW BATTERY

PPL51150ER

* Standard as per AIS156



RATING

Voltage Ratings (Volts) : 51.2
Battery Capacity (Ah) : 150
Power Rating (kWh) : 7.68



COMMUNICATION OPTIONS

- Bluetooth
- CAN (Optional)
- UART/RS485 (Optional)
- IoT (Optional) - Cloud Storage, Real Time Performance Analytics, Battery Swapping Analytics, Asset Tracking, SOC Monitoring, Fleet Management



ELELCTRICAL PARAMETERS

- Operating Voltage Range (Volts) : $44.0 \sim 58.4 \pm 1.0$
- Maximum Charging Current : 0.5C
- Maximum Discharge Current : 1C Continuous



CELL CYCLE LIFE

≥ 2000



BMS PROTECTION

- Over-charge Protection
- Over-discharge Protection
- Over-current Protection
- Over-temperature Protection
- Short-circuit Protection
- Audio & Visual Alarm



BALANCING MODE

ACTIVE



CHARGER SPECIFICATION

- Charging Voltage (Volts) : 58.0 ± 0.5
- Charging Current (Amps) : 30.0 ± 0.5
- Charging Mode : Precharge - CC - CV
- CAN Enabled (Optional)
- LED Display (Optional)
- Earth Leakage Protection
- Reverse Polarity Protection
- Failure Sensing



OPERATING CONDITIONS

- Charging Temperature (Deg.C) : $-5 \sim 55$
- Discharging Temperature (Deg.C) : $-10 \sim 60$
- Storage Temperature (Deg.C) : $0 \sim 35$



OUTPUT INTERFACE

SB 75 / SB 50



WEATHER SEALING RATING

IP67



FIRE RESISTANCE

YES




KEY FEATURES

- High Energy Density
- Long Cycle Life
- Fast Charging
- Low Self-Discharge
- Smart Battery Management

E-RIKSHAW BATTERY

PPL51200ER

* Standard as per AIS156



RATING

Voltage Ratings (Volts) : 51.2
Battery Capacity (Ah) : 200
Power Rating (kWh) : 10.44



COMMUNICATION OPTIONS

- Bluetooth
- CAN (Optional)
- UART/RS485 (Optional)
- IoT (Optional) - Cloud Storage, Real Time Performance Analytics, Battery Swapping Analytics, Asset Tracking, SOC Monitoring, Fleet Management



ELELCTRICAL PARAMETERS

- Operating Voltage Range (Volts) : $44.0 \sim 58.4 \pm 1.1$
- Maximum Charging Current : 0.5C
- Maximum Discharge Current : 1C Continuous



CELL CYCLE LIFE

≥ 2000



BMS PROTECTION

- Over-charge Protection
- Over-discharge Protection
- Over-current Protection
- Over-temperature Protection
- Short-circuit Protection
- Audio & Visual Alarm



BALANCING MODE

ACTIVE



CHARGER SPECIFICATION

- Charging Voltage (Volts) : 58.0 ± 0.6
- Charging Current (Amps) : 5.0 ± 0.6
- Charging Mode : Precharge - CC - CV
- CAN Enabled (Optional)
- LED Display (Optional)
- Earth Leakage Protection
- Reverse Polarity Protection
- Failure Sensing



OPERATING CONDITIONS

- Charging Temperature (Deg.C) : $-5 \sim 55$
- Discharging Temperature (Deg.C) : $-10 \sim 60$
- Storage Temperature (Deg.C) : $1 \sim 35$



OUTPUT INTERFACE

SB 75 / SB 51



WEATHER SEALING RATING

IP67



FIRE RESISTANCE

YES



KEY FEATURES

- High Energy Density
- Long Cycle Life
- Fast Charging
- Low Self-Discharge
- Smart Battery Management

CUSTOMISATION

We can customise and produce for you!



E-RIKSHAW BATTERY



2-WHEELER BATTERY



SOLAR BATTERY



ENERGY STORAGE SYSTEM



**PITBULL
POWER**

CONTACT US



PHONE NO.

+91 92899 73394, +91 124 4469029



EMAIL

info@pitbullpower.in



WEBSITE

www.pitbullpower.in



ADDRESS

114, Udyog Vihar, Phase IV, Gurgaon
122015, Haryana, India